

# PERCUSSION DETONATOR UD-M76P1

## APPLICATION

The percussion detonator UD-M76P1 is the assembly of fuse UBR-M75P1 which is consisted of initial cap, delay device, transit initial powder and detonator powder. It is assigned to, in the assembly of fuse UBR-M75P1, bring up the explosive powder charge to detonation.

## TECHNICAL SPECIFICATIONS

<b>Length</b>	70 mm
<b>Diameter</b>	12 mm
<b>Weight</b>	13 g
<b>Thread</b>	M10x0.75
<b>Delay time</b>	3 - 4.4 s
<b>Operating temperature</b>	from -10°C to +50°C
<b>UN Number</b>	0361
<b>ADR Number</b>	1.4B



## PACKING

Standard packing consists of 100 percussion detonators in one carton box.  
Dimensions 100 x 100 x 75 mm.

9 carton boxes (900 percussion detonators) in one metal box.  
Dimensions 306 x 156 x 192 mm.

4 metal boxes (3600 percussion detonators) in one wooden box.  
Dimensions 710 x 370 x 290 mm.

## STORAGE

Keep on dry place, in the warehouse with good ventilation on the temperature from -10 ° to +30 °C.

## SHELF LIFE

12 months, under storing condition.

10 years build-in in the hand bomb in above mentioned and prescribed storing conditions.